

# 

# **CFORCE EPS LX**

## TOP FEATURES

400cc engine with BOSCH injection & ignition system(30.5 HP/24.3 ft/lb)

Adjustable hydraulic shock absorbers in 5 positions for spring preloading (Elka Shocks)

**Continuously Variable Transmission** (CVTech-IBC)

**Electric Power Steering (EPS)** 

2500 lb complete winch assembly

Hitch towing rating: 400 kg

Digital display dashboard with full instrumentation

12V outlet and dual USB outlet

**Mirrors** 

LED headlights with integrated turn signals



## **CF MOTO WARRANTY**

CFMOTO Canada's standard 5-year warranty includes a 12-month manufacturer limited warranty and a 48-month powertrain limited warranty

5 Year Limited warranty: 1 year full + balance 48 months powertrain only or 5000 km.













4-Wheels Drive Clutch on Demand

Electric Power Steering

**Lateral Mirrors** 

**CVTech Clutch** System

**BOSCH Engine** Management

## PECIFICATIONS

#### **ENGINE**

**Type:** Single-cylinder, 4-valves, 4 strokes

Displacement: 400 cc

Engine Management: BOSCH EFI &

Ignition

Maximum Torque: 24.3 Ft./Lb. @ 6000

Maximum Power Output: 30.5 HP @

7200 RPM

Cooling System: Liquid Starting: Electric Battery: 30 Amp **SIZE & WEIGHT** 

L x W x H: 2100 x 1100 x 1150 mm (82.7

x 43.3 x 45.3 in)

Wheelbase: 1260 mm (49.6 in) **Seat Height:** 530 mm (20.9 in) Ground Clearance: 250 mm (9.8 in) Fuel Tank Capacity: 14 L (3.7 Gal) Vehicle Weight with All Fluids: 345 Kg

(760 Lbs)

Towing Capacity: 281 Kg (620 Lbs)

Rear Box Capacity: 20 Kg (44 Lbs) / 40 Kg Rear Travel: 170 mm (88 Lbs)

#### WHEELS

Front Wheels: Aluminum alloy (12 x 6 in) Rear Wheels: Aluminum alloy (12 x 7.5 in) Front Tires: AT 25 x 8-12 (Innova Mud Gear Lite)

Rear Tires: AT 25 x 10-12 (Innova Mud Gear Lite)

**BRAKES** 

Brakes: Front and rear brake disc system

TRANSMISSION

CV-Tech IBC Clutch System: Variable

transmission

Power Train: 2WD/4WD, electric locking

differential

#### SUSPENSION AND STEERING

Front Suspension: Double arm independent suspension, hydraulic shock

absorber, five adjustments spring

preloads

Front Travel: 170 mm

Rear Suspension: Double arm

independent suspension, hydraulic shock absorber, five adjustments spring

preloads

Steering: Electronic Power Steering (EPS)

## CFMOTO.CA | CHOPPERSCUSTOMWORKS.CA

For additional information, please call us!

905-774-1112